

# Hydraulic Hose


# Wire Braid



## RIVAFLEX

## DIN EN853 2SN

**DIN EN 853 2 SN**  
Exceeds SAE100R2AT



### Hose Construction:

Tube: oil resistant synthetic rubber  
Reinforcement: two high tensile steel wire braids  
Cover: abrasion and weather resistant synthetic rubber  
Germanischer Lloyds Flame Resistant Certified  
Temperature range: -40°C to +100°C (+120°C max.)

Part #	Nominal Ø		Inside Ø mm	Braid Ø mm	Outside Ø mm	Working pressure		Test pressure bar	Min burst pressure bar	Bend radius mm	Weight kg/m
	Dash	inch				bar	psi				
2SN-4	-4	1/4	6.4	12.7	15.0	400	5805	960	1600	100	0.33
2SN-6	-6	3/8	9.5	16.7	19.0	330	4790	795	1320	130	0.50
2SN-8	-8	1/2	12.7	19.8	22.2	275	3990	660	1100	180	0.59
2SN-10	-10	5/8	15.9	23.0	25.4	250	3625	600	1000	200	0.71
2SN-12	-12	3/4	19.0	27.0	29.3	215	3120	510	850	240	0.86
2SN-16	-16	1	25.4	34.9	38.1	165	2395	390	650	300	1.28