
CSSERIES

INTERCHANGE > **Stucchi profile (only for Stucchi multicouplings)**





TECHNICAL FEATURES AND OPTIONS

Interchange
Stucchi profile (only for Stucchi multicouplings)

Sealing description
Nitrile NBR

Connection system
By multicoupling

Available sizes
from 3/8" to 1/2"

Material /treatment
Brass

Available threads
BSP - NPT

Operating pressure
Up to 10 bar


Locking mechanism
PIN/CAM

Flow rate
Up to 90 l/min

Temperature (°C)
oil -20°/+100°
water +5°/+60°

Valving style
Flat face

Connection under pressure
Connection: not allowed
Disconnection: not allowed.



BENEFITS

- The solution to conduct low pressure hydraulic oil,pneumatic or water lines.
- Valving design helps to reduce the inclusion of contamination to the circuit.
- Minimal fluid loss during connection / disconnection, reducing fluid loss to the environment.
- Minimal air inclusion during connection / disconnection, enhancing correct function of the circuit.
- Linear flow reduces internal turbulence and pressure drop, maintaining circuit efficiency in the entire system.
- Good corrosion resistance thanks to brass components construction
- The modular design allows flexibility with the range of port configurations (hose barb available on request).
- Allows to conduct in the same multiconnection different fluids:hydraulic oil, water, air.
- Couplings are assembled with a seeger ring for a quicker mounting or service on the multiconnection.
- Compact slim design.
- Safe and simple to use.

HOW TO USE

- See instructions at page 163.

MAIN APPLICATIONS



PERFORMANCE

Size		Series/Size	Max. flow suggested		Spillage*
Inch	mm (ISO)		l/min	gpm	ml
3/8	-	CS9	46	12.2	0.03
1/2	-	CS12	90	23.8	0.04

Size	Series/Size	Max. operating pressure						Burst pressure					
		Coupled		Male		Female		Coupled		Male		Female	
Inch		MPa	psi	MPa	psi	MPa	psi	MPa	psi	MPa	psi	MPa	psi
3/8	CS9	1	145	1	145	1	145	4	580	4	580	4	580
1/2	CS12	1	145	1	145	1	145	4	580	4	580	4	580

* Spillage is an indicative value of the fluid loss per couple-uncouple cycle.

Different possible configurations:
Other ports available upon request.
Different threads available upon request.
PL version, free flow (without valve) on both sides.

Temperature range:
Seals in NBR (Nitrile):
- for oil, from -20° C to +100° C (from -4° F to +212° F)
- for water, from +5° C + 60° C (from +41° F to +140° F)
Upon request seals in FKM (VITON®): from -15°C to +180°C (from +5 °F to +356 °F).

Tests:
The couplings have been tested in according with ISO norm.


WARNING

A defect, a wrong choice or an improper use of products, can cause injury to persons, animals and objects.
Never connect or disconnect with dynamic pressure (e.g. pump on).
Do not use the female coupling disconnected with high impulse pressure.
Do not couple-uncouple with flow and/or pressure in the circuit.
Do not couple-uncouple when the temperature inside of the circuit is higher than 80 °C (176 °F).
Check the maximum allowable operating pressure of the port in use.
Make sure that the medium used is compatible with seal and material as indicated for each series.
In case of doubt please contact Stucchi Technical Support.
It is MANDATORY to read and closely follow the instructions. Last updated version always apply at time of installation, see latest written Instructions on Stucchi website (stucchigroup.com) before selecting or using Stucchi products.


Please read carefully General instructions for selection and use of the products in our master catalogues.
Do not couple-uncouple with flow and/or dynamic pressure in the circuit.
CS series is intended to be used only on Stucchi Multiconnections. Do not use the CS coupling on a Custom-made multiconnection or other device different than a Stucchi Multiconnection.
Do not disassemble, misuse, modify or damage the products.
CS series has been tested&approved with hydraulic oil. CS serie is intended to be used only with not dangerous fluids (water, hydraulic oil, air at low temperature/low pressure).
Do not use CS couplings with dangerous, inflammable or explosive fluids (steam, acids, very hot/flammable oils etc.).
Do not use CS couplings with very hot fluids (limits given by NBR seal compatibility&temperature range).
Do not use CS couplings with fluids below the freezing point to avoid damages due to ice expansion and consequential extrusion of the valving.

SPECIFICATIONS

FEMALE



MALE



Port description: FEMALE THREAD BSPP (ISO 1179-1)

Body size	Descriptive Code	Item Code		Port (A)	Hex			Weight	
						mm	in	kg	lb
3/8”	**F CSF9BN 3/8 BSP**	Female	**802100002**	3/8”	C	27,0	1,06	0,19	0,41
	M CSM9BN 3/8 BSP	Male	**802100003**		B	27,0	1,06	0,16	0,36
3/8”	**F CSF9BN 1/2 BSP**	Female	**802100006**	1/2”	C	27,0	1,06	0,18	0,39
	M CSM9BN 1/2 BSP	Male	**802100007**		B	27,0	1,06	0,16	0,34
1/2”	**F CSF12BN 1/4 BSP**	Female	**802100000**	1/4”	C	30,0	1,18	0,23	0,51
	M CSM12BN 1/4 BSP	Male	**802100001**		B	30,0	1,18	0,20	0,45
1/2”	**F CSF12BN 1/2 BSP**	Female	**802100008**	1/2”	C	30,0	1,18	0,24	0,52
	M CSM12BN 1/2 BSP	Male	**802100009**		B	30,0	1,18	0,22	0,48

Port description: FEMALE THREAD NPT (ANSI B1.20.1)


Body size	Descriptive Code	Item Code		Port (A)	Hex			Weight	
						mm	in	kg	lb
3/8”	**F CSF9BN 3/8 NPT**	Female	**802101000**	3/8”	C	24,0	0,94	0,15	0,32
	M CSM9BN 3/8 NPT	Male	**802101003**		B	24,0	0,94	0,13	0,28
1/2”	**F CSF12BN 1/2 NPT**	Female	**802101004**	1/2”	C	30,0	1,18	0,24	0,52
	M CSM12BN 1/2 NPT	Male	**802101005**		B	30,0	1,18	0,21	0,45



SPARE KIT SEAL FOR FEMALE


Repair kit		
Body Size	Description	Part Number
3/8”	SET OF 10 EXTERNAL OR CSF9	815701060
1/2”	SET OF 10 EXTERNAL OR CSF12	815701062

O-Ring in Nitrile
(kit composed of 10 O-Ring for female coupling; 1 female = 1 O-Ring)



REPAIR SEEGER

Repair kit seeger	
Part Number	Description
815701103	SET OF 10 SEEGER CSF9-CSM12
815701104	SET OF 10 SEEGER CSM9
815701105	SET OF 10 SEEGER CSF12



STUCCHI MultiCouplings Catalog - April 2026 - All right reserved.
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service.