Stucchi®

Experts in quick couplings since 1960



For over 60 years, Stucchi is one of the leading manufacturers of quick disconnect couplings.

With a wide variety of sizes and port configurations ranging from 1/8" to 2" suitable for some of the most demanding applications.

To compliment our core product we offer the FCP range which includes swivels, suregrips, check, ball and flow control valves.

Our solutions-based approach meets the demanding requirements for applications across multiple markets.

INSIST ON THE BRAND

EUROPEAN STUCCHI QUALITY

A SERIES



Valving Style: **Flat face**
Interchange: **ISO 16028**
Sealing description: **Nitrile NBR**
Available sizes: **From 1/8" to 1-1/2"**
Operating Pressure: **Up to 420 bar**
Flow rate: **Up to 750 L/min**
Material/treatment:
Carbon steel/Cr3

SATURN SERIES



Valving Style: **Flat face**
Interchange: **ISO 16028**
(for the couplings)
Available sizes: **From 1/2" to 3/4"**
Operating Pressure: **Up to 350 bar**
Flow rate: **Up to 200 L/min**
Material/treatment:
Carbon steel/Cr3
Connection system: **Push**
Connection under pressure:
One side + disconnection allowed (using Knob)

VEP-HD SERIES



Valving style: **Flat face**
Interchange: **Stucchi profile**
Available sizes: **From 3/4" to 1-1/2"**
Operating pressure: **Up to 550 bar**
Flow rate: **Up to 750 l/min**
Material: **Carbon steel/QPQ**
Connection system: **Screw**
Connection under pressure:
Both side, easy connection + disconnection allowed

SOLUTIONS

EARTHMOVING

Dandenong South, Victoria Ph: +61 3 9793 4611
Malaga, Western Australia Ph: +61 8 6365 4868
Brendale, Queensland Ph: +61 7 3495 0222
East Tamaki, New Zealand Ph: +64 800 005 905 | info@stucchinz.com | stucchinz.com
info@stucchiaustralia.com | stucchiaustralia.com

Stucchi® | FCP


Stucchi®

Experts in quick couplings since 1960

BALL VALVES

COUPLINGS

FE2 SERIES



Number of Ports: **2**
Material: **Available in carbon steel and stainless steel**
Available Sizes: **¼ to 1”**
Port: **NPT, BSP, SAE, Flange**
Operating Pressure: **Up to 500 bar**
Temperature range: **-60 + 230 °C (dependent on body and seal material)**

GV2 SERIES



Number of Ports: **2**
Material: **Carbon steel**
Available Sizes: **1/8” to 1-1/4”**
Thread: **NPT, BSP, SAE, Flange**
Operating Pressure: **Up to 500 bar**
Temperature range: **-20 + 230 °C**
Typical use: **Ideal for excavator boom mounting**

VP-P SERIES



Valving style: **Flat face**
Interchange: **Stucchi profile**
Available sizes: **From 1/4” to 1-1/2”**
Operating Pressure: **Up to 600 bar**
Flow rate: **Up to 750 L/Min**
Material/treatment: **Carbon steel/Cr3+QPQ**
Connection system: **Screw**
Connection under pressure: **Both side, easy connection + disconnection allowed**

VEP-P SERIES



Valving style: **Flat face**
Interchange: **Stucchi profile**
Available Sizes: **From 1/4” to 2”**
Operating Pressure: **Up to 600 bar**
Flow rate: **Up to 1000 L/min**
Material/treatment: **Carbon steel/Cr3+QPQ**
Connection system: **Screw**
Connection under pressure: **Both side, easy connection + disconnection allowed**

APM SERIES



Valving style: **Flat face**
Interchange: **ISO 16028 and NFPA T3.20.15 HTMA (size 3/8”)**
Available Sizes: **From 3/8” to 1-1/2”**
Operating Pressure: **Up to 350 bar**
Flow rate: **Up to 750 L/Min**
Material/treatment: **Carbon steel/Cr3**
Connection system: **Push**
Connection under pressure: **Male side, other side to drain**

A-HD SERIES



Valving style: **Flat face**
Interchange: **ISO 16028 and NFPA T3.20.15 HTMA (size 3/8”)**
Available Sizes: **From 3/8” to 1/2”**
Operating Pressure: **Up to 350 bar**
Flow rate: **Up to 90 L/Min**
Material/treatment: **Carbon steel/Cr3**
Connection systemt: **Push**
Connection under pressure: **Female side, other side to drain**

VD SERIES



Valving style: **Flat face limited spill**
Interchange: **Similar Couplings (Rohrleitung)**
Available Sizes: **From 3/8” to 1-1/4”**
Operating Pressure: **Up to 420 bar**
Flow rate: **Up to 576 L/Min**
Material/treatment: **Carbon steel/Cr3**
Connection system: **Screw**
Connection under pressure: **One side**

ACCESSORIES



Available: **Caps & Plugs, Parking Stations, Seal & Repair Kits, Anodised Colour Coding**

Dandenong South, Victoria Ph: +61 3 9793 4611
Malaga, Western Australia Ph: +61 8 6365 4868
Brendale, Queensland Ph: +61 7 3495 0222
East Tamaki, New Zealand Ph: +64 800 005 905 | info@stucchinz.com | stucchinz.com
info@stucchiaustralia.com | stucchiaustralia.com

Stucchi® | FCP