Stucchi®

Experts in quick couplings since 1960



For over 60 years, Stucchi is one of the leading manufacturers of quick disconnect couplings.

With a wide variety of sizes and port configurations ranging from 1/8" to 2" suitable for some of the most demanding applications.

To compliment our core product we offer the FCP range which includes swivels, suregrips, check, ball and flow control valves.

Our solutions-based approach meets the demanding requirements for applications across multiple markets.

INSIST ON THE BRAND

EUROPEAN STUCCHI QUALITY

IRC SERIES



Valving Style: **Poppet**
Interchange: **similar couplings (Nordic interface)**
Available sizes: **From 1/4" to 1"**
Operating Pressure: **Up to 600 bar**
Flow rate: **Up to 378 L/min**
Material / Treatment: **Carbon steel / Cr3**
Connection system: **Single acting sleeve**
Connection under pressure: **One side with PC version**

FIRG SERIES



Valving Style: **Flat face**
Interchange: **ISO 16028 and NFPA T3.20.15 HTMA (size 3/8")**
Available sizes: **From 1/8" to 1-1/2"**
Configuration: **Modular construction**
Operating Pressure: **Up to 420 bar**
Flow rate: **Up to 750 L/Min**
Material / Treatment: **Carbon steel/ Cr3 (Zi-Ni version available)**
Connection system: **Push**
Connection under pressure: **Not allowed**

SJ SERIES



Available Size: **From DN6 to DN50**
Operating pressure: **Up to 400 bar**
Ends: **BSP - NPT**
Material/treatment: **316L, Carbon Steel**
Connection system: **Screw**
Profile: **Straight & 90 degree**

GR SERIES



Valving style: **Flat face**
Interchange: **Stucchi profile**
Available sizes: **From 3/8" to 1"**
Operating pressure: **Up to 350 bar**
Flow rate: **Up to 378 L/min**
Material: **Brass & high strength carbon steel**
Connection system: **Lever**
Connection under pressure: **Both side, easy connection**

SOLUTIONS

TRANSPORT

Dandenong South, Victoria Ph: +61 3 9793 4611
Malaga, Western Australia Ph: +61 8 6365 4868
Brendale, Queensland Ph: +61 7 3495 0222
East Tamaki, New Zealand Ph: +64 800 005 905 | info@stucchinz.com | stucchinz.com
info@stucchiaustralia.com | stucchiaustralia.com

Stucchi® | FCP

Stucchi®


Experts in quick couplings since 1960

BALL VALVES

COUPLINGS


CHECK VALVES

FE2 SERIES



Number of Ports: **2**
Material: **Available in carbon steel and stainless steel**
Available Sizes: **¼ to 1”**
Port: **NPT, BSP, SAE, Flange**
Operating Pressure: **Up to 500 bar**
Temperature range: **-60 + 230 °C (dependent on body and seal material)**

FE3 SERIES



Number of Ports: **3**
Port Type: **L and T**
Material: **Available in carbon steel and stainless**
Available Sizes: **¼ to 1”**
Port: **NPT, BSP**
Operating Pressure: **Up to 400 bar**
Temperature range: **-60 + 230 °C (dependent on body and seal material)**

IRN SERIES



Valving style: **Poppet**
Interchange: **Similar Couplings**
Available sizes: **1”**
Operating Pressure: **Up to 300 bar**
Flow rate: **Up to 378 L/min**
Material / Treatment: **High strength carbon steel**
Connection system: **Single active sleeve**
Connection under pressure: **Not allowed**

VSB SERIES



Valving style: **Poppet**
Interchange: **Similar Couplings**
Available sizes: **From 3/4” to 1 1/2”**
Operating Pressure: **Up to 200 bar**
Flow rate: **Up to 300 L/Min**
Material: **brass (body), steel (wing nut)**
Connection system: **Screw**
Connection under pressure: **One side**

BIR SERIES



Valving style: **Poppet**
Interchange: **ISO 7241-1 “A”**
Available Sizes: **From 1/4” to 2”**
Operating Pressure: **Up to 350 bar**
Flow rate: **Up to 1000 L/min**
Material: **Carbon steel/Cr3**
Connection system: **Single acting sleeve**
Connection under pressure:: **One side with PC version**

VD SERIES



Valving style: **Poppet**
Interchange: **ISO14541**
Available Sizes: **From 1/4” to 1-1/4”**
Operating Pressure: **Up to 450 bar**
Flow rate: **Up to 378 L/Min**
Material/treatment: **Carbon steel/Cr3**
Connection system: **Screw**
Connection under pressure: **One side**

VUZ SERIES



Available Sizes: **From 1/8” to 2”**
Operating Pressure: **Up to 400 bar**
Flow rate: **Up to 1000 L/min**
Material / Treatment: **Carbon steel / Cr3**

ACCESSORIES



Available: **Caps & Plugs, Parking Stations, Seal & Repair Kits, Anodised Colour Coding**

Dandenong South, Victoria Ph: +61 3 9793 4611
Malaga, Western Australia Ph: +61 8 6365 4868
Brendale, Queensland Ph: +61 7 3495 0222
East Tamaki, New Zealand Ph: +64 800 005 905 | info@stucchinz.com | stucchinz.com
info@stucchiaustralia.com | stucchiaustralia.com

Stucchi® | FCP