M UQD02B 1/4 SAE EXT

Codice articolo: **813704235** / **Macho**

Estilo de válvula Cara plana	**Dimensión** 02
Sellado EPDM	**Intercambio** OCP
Sistema de conexión Push	**Sistema de desconexión** Tirar el manguito hacia atrás
Material Acciaio inossidabile (AISI 303)	**Mecanismo de bloqueo** Perno di ritenuta
Desconexión con presión No	**Roscas** FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)
Conexión con presión residual No	**Temperatura** -40 / +75 °C; -40 / +167 °F
Aplicaciones Centro de datos	

Rendimiento	IMPERIAL
Presión de trabajo máxima - acoplado (psi)	160
Presión de trabajo - desacoplado (psi)	160
Presión de ruptura - acoplado (psi)	580
Presión de ruptura - acoplado (psi)	580
Fuerza de conexión (lbf)	14
Pérdida (ml)	0,01

Tamaño	IMPERIAL
Dimensión roscas (A)	7/16-20 UNF
Longitud total M+F (in)	2,7
Longitud (in)	1,37
Diámetro máximo (in)	0,61
Peso (lb)	0,31

Productos relacionados

Código de producto	Tipologia	Nombre del producto
813723234	Femmina	F UQD02B 1/4 HB

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service