F UQD06R 1/2 HB

Codice articolo: **813723216** / **Hembra**

Estilo de válvula Cara plana	**Dimensión** 06
Sellado EPDM	**Intercambio** OCP
Sistema de conexión Push	**Sistema de desconexión** Tirar el manguito hacia atrás
Material Acciaio inossidabile (AISI 303)	**Mecanismo de bloqueo** Perno di ritenuta
Desconexión con presión No	**Roscas** HOSE BARB COMPATIBLE WITH PARKER PUSH-LOK®
Conexión con presión residual No	**Temperatura** -40 / +75 °C; -40 / +167 °F
Aplicaciones Centro de datos	

Rendimiento	METRIC
Presión de trabajo máxima - acoplado (MPa)	1,1
Presión de trabajo - desacoplado (MPa)	1,1
Presión de ruptura - acoplado (MPa)	4
Presión de ruptura - desacoplado (MPa)	4
Fuerza de conexión (N)	80
Pérdida (ml)	0,02

Tamaño	METRIC
Dimensión roscas (A)	15.2
Longitud (mm)	83,3
Diámetro máximo (mm)	31
Peso (kg)	0,1

Productos relacionados

Código de producto	Tipologia	Nombre del producto
813704217	Maschio	M UQD06R 1/2 SAE EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service