F IFR8 1/2 BSP

Codice articolo: **800200050** / **Hembra**

Estilo de válvula Cara plana non spill	**Dimensión** 3/8"
Sellado Nitrile NBR	**Tratamiento** Cr3
Intercambio ISO 5676 "NF U 16-006"	**Sistema de conexión** Tirar el manguito hacia atrás y empujar
Sistema de desconexión Tirar el manguito hacia atrás	**Material** Acero al carbono
Mecanismo de bloqueo Bola de bloqueo	**Desconexión con presión** No
Roscas FEMALE THREAD BSPP (ISO 1179-1)	**Conexión con presión residual** No
Temperatura -20 / +100 °C; -4 / +212 °F	**Aplicaciones** Maquinaria agrícola, Implementos agrícolas, Agricultura

Rendimiento	METRIC
ISO DN (mm)	6.3
Caudal máximo (l/min)	46
Presión de trabajo máxima - acoplado (MPa)	15
Presión de trabajo - desacoplado (MPa)	15
Presión de ruptura - acoplado (MPa)	100
Presión de ruptura - desacoplado (MPa)	30
Fuerza de conexión (N)	170
Fuerza de desconexión (N)	27
Pérdida (ml)	0.06

Tamaño	METRIC
Dimensión roscas (A)	G 1/2"
Longitud total M+F (mm)	F+D-15
Longitud (mm)	59,2
Diámetro máximo (mm)	44
Peso (kg)	0,43

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service