
M I12GS 3/4 BSP*

Codice articolo: **809400021** / **Macho** / ***Prodotto disponibile su richiesta**



Estilo de válvula Cabezal	**Dimensión** 1/2"
Sellado Nitrile NBR	**Tratamiento** Cr3
Intercambio ISO 7241 A	**Sistema de conexión** Push
Sistema de desconexión Pull	**Material** Acero al carbono
Mecanismo de bloqueo Bola de bloqueo	**Desconexión con presión** No
Roscas FEMALE THREAD BSPP (ISO 1179-1)	**Conexión con presión residual** No
Temperatura -20 / +100 °C; -4 / +212 °F	**Aplicaciones** Maquinaria agrícola, Implementos agrícolas, Agricultura

Rendimiento	IMPERIAL
ISO DN (mm)	12.5
Caudal máximo (gpm)	23.85
Presión de trabajo máxima - acoplado (psi)	3625
Presión de trabajo - desacoplado (psi)	3625
Presión de ruptura - acoplado (psi)	13050
Presión de ruptura - acoplado (psi)	14500
Fuerza de conexión (lbf)	20,25
Fuerza de desconexión (lbf)	18
Pérdida (ml)	1.8

Tamaño	IMPERIAL
Dimensión roscas (A)	3/4"
Longitud total M+F (in)	4,84
Longitud (in)	2,69
Diámetro máximo (in)	1,57
Peso (lb)	0,52

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service