
# M I12GS L8

Codice articolo: **809408003** / **Macho**




| | |
|---|---|
| **Estilo de válvula**<br>Cabezal | **Dimensión**<br>1/2" |
| **Sellado**<br>Nitrile NBR | **Tratamiento**<br>Cr3 |
| **Intercambio**<br>ISO 7241 A | **Sistema de conexión**<br>Push |
| **Sistema de desconexión**<br>Pull | **Material**<br>Acero al carbono |
| **Mecanismo de bloqueo**<br>Bola de bloqueo | **Desconexión con presión**<br>No |
| **Roscas**<br>MALE THREAD METRIC L - 24° CONE (ISO 8434-1 & DIN 2353) | **Conexión con presión residual**<br>No |
| **Temperatura**<br>-20 / +100 °C; -4 / +212 °F | **Aplicaciones**<br>Maquinaria agrícola, Implementos agrícolas, Agricultura |

| Rendimiento | METRIC |
|---|---|
| ISO DN (mm) | 12.5 |
| Caudal máximo (l/min) | 90 |
| Presión de trabajo máxima - acoplado (MPa) | 25 |
| Presión de trabajo - desacoplado (MPa) | 25 |
| Presión de ruptura - acoplado (MPa) | 90 |
| Presión de ruptura - desacoplado (MPa) | 100 |
| Fuerza de conexión (N) | 90 |
| Fuerza de desconexión (N) | 80 |
| Pérdida (ml) | 1.8 |

| Tamaño | METRIC |
|---|---|
| Dimensión roscas (A) | M14x1.5 |
| Longitud total M+F (mm) | 101 |
| Longitud (mm) | 57,3 |
| Diámetro máximo (mm) | 20,5 |
| Peso (kg) | 0,12 |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service