# M UQD06R 1/2 SAE EXT

Codice articolo: **813704217** / **Macho**

| | |
|---|---|
| **Sistema de vedação**<br>Face Plana | **Tamanho do acoplamento**<br>06 |
| **Vedação**<br>EPDM | **Intercambiabilidade**<br>OCP |
| **Sistema de conexão**<br>Empurrar | **Sistema de desconexão**<br>Puxar o luva para trás |
| **Material**<br>Acciaio inossidabile (AISI 303) | **Mecanismo de trava**<br>Perno di ritenuta |
| **Desconexão sob pressão**<br>Não | **Rosca**<br>FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1) |
| **Conexão com pressão residual**<br>Não | **Temperatura**<br>-40 / +75 °C; -40 / +167 °F |
| **Aplicações**<br>Data Center | |

| Desempenho | METRIC |
|---|---|
| Pressão de trabalho máxima - acoplado (MPa) | 1,1 |
| Pressão de trabalho - desacoplado (MPa) | 1,1 |
| Pressão de ruptura - acoplado (MPa) | 4 |
| Pressão de ruptura - desacoplado (MPa) | 4 |
| Força de conexão (N) | 80 |
| Vazamento (ml) | 0,02 |

| Tamanho | METRIC |
|---|---|
| Tamanho da conexão (A) | 3/4-16UNF |
| Comprimento (mm) | 52,8 |
| Diâmetro máximo (mm) | 25 |
| Peso (kg) | 0,06 |

Produtos relacionados

| Código de produto | Tipologia | Nome do produto |
|---|---|---|
| 813723216 | Femmina | F UQD06R 1/2 HB |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service