M UQD06B 1/2 SAE EXT

Codice articolo: **813704251** / **Macho**

Sistema de vedação Face Plana	**Tamanho do acoplamento** 06
Vedação EPDM	**Intercambiabilidade** OCP
Sistema de conexão Empurrar	**Sistema de desconexão** Puxar o luva para trás
Material Acciaio inossidabile (AISI 303)	**Mecanismo de trava** Perno di ritenuta
Desconexão sob pressão Não	**Rosca** FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)
Conexão com pressão residual Não	**Temperatura** -40 / +75 °C; -40 / +167 °F
Aplicações Data Center	

Desempenho	IMPERIAL
Pressão de trabalho máxima - acoplado (psi)	160
Pressão de trabalho - desacoplado (psi)	160
Pressão de ruptura - acoplado (psi)	580
Pressão de ruptura - desacoplado (psi)	580
Força de conexão (lbf)	18
Vazamento (ml)	0,02

Tamanho	IMPERIAL
Tamanho da conexão (A)	3/4-16UNF
Comprimento total M+F (in)	4,1
Comprimento (in)	2,1
Diâmetro máximo (in)	1
Peso (lb)	0,13 0,37

Produtos relacionados

Código de produto	Tipologia	Nome do produto
813723250	Femmina	F UQD06B 1/2 HB

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service