F UQD04R 3/8 HB

Codice articolo: **813723208** / **Fêmea**

Sistema de vedação Face Plana	**Tamanho do acoplamento** 04
Vedação EPDM	**Intercambiabilidade** OCP
Sistema de conexão Empurrar	**Sistema de desconexão** Puxar o luva para trás
Material Acciaio inossidabile (AISI 303)	**Mecanismo de trava** Perno di ritenuta
Desconexão sob pressão Não	**Rosca** HOSE BARB COMPATIBLE WITH PARKER PUSH-LOK®
Conexão com pressão residual Não	**Temperatura** -40 / +75 °C; -40 / +167 °F
Aplicações Data Center	

Desempenho	IMPERIAL
Pressão de trabalho máxima - acoplado (psi)	160
Pressão de trabalho - desacoplado (psi)	160
Pressão de ruptura - acoplado (psi)	580
Pressão de ruptura - desacoplado (psi)	580
Força de conexão (lbf)	20
Vazamento (ml)	0.01

Tamanho	IMPERIAL
Tamanho da conexão (A)	11.9
Comprimento total M+F (in)	3,72
Comprimento (in)	3
Diâmetro máximo (in)	1,02
Peso (lb)	0,29

Produtos relacionados

Código de produto	Tipologia	Nome do produto
813704209	Maschio	M UQD04R 3/8 SAE EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service