F UQD06R 1/2 HB

Codice articolo: **813723216** / **Fêmea**

Sistema de vedação Face Plana	**Tamanho do acoplamento** 06
Vedação EPDM	**Intercambiabilidade** OCP
Sistema de conexão Empurrar	**Sistema de desconexão** Puxar o luva para trás
Material Acciaio inossidabile (AISI 303)	**Mecanismo de trava** Perno di ritenuta
Desconexão sob pressão Não	**Rosca** HOSE BARB COMPATIBLE WITH PARKER PUSH-LOK®
Conexão com pressão residual Não	**Temperatura** -40 / +75 °C; -40 / +167 °F
Aplicações Data Center	

Desempenho	METRIC
Pressão de trabalho máxima - acoplado (MPa)	1,1
Pressão de trabalho - desacoplado (MPa)	1,1
Pressão de ruptura - acoplado (MPa)	4
Pressão de ruptura - desacoplado (MPa)	4
Força de conexão (N)	80
Vazamento (ml)	0,02

Tamanho	METRIC
Tamanho da conexão (A)	15.2
Comprimento (mm)	83,3
Diâmetro máximo (mm)	31
Peso (kg)	0,1

Produtos relacionados

Código de produto	Tipologia	Nome do produto
813704217	Maschio	M UQD06R 1/2 SAE EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service