F IV38HP BSP EXT DIN3852-2-B*

Codice articolo: **800200028** / **Fêmea** / ***Prodotto disponibile su richiesta**

Sistema de vedação Esfera	**Tamanho do acoplamento** 3/8"
Vedação Nitrile NBR	**Tratamento** Cr3
Intercambiabilidade ISO14540 (Alta Pressão)	**Sistema de conexão** Parafuso
Sistema de desconexão Desenroscar	**Material** Aço carbono de alta resistência
Mecanismo de trava Parafuso para conexão	**Desconexão sob pressão** Não
Rosca MALE THREAD METRIC DIN3852-1-A	**Conexão com pressão residual** Não
Temperatura -20 / +100 °C; -4 / +212 °F	**Aplicações** Equipamentos de resgate, Ferramentas hidráulicas

Desempenho	IMPERIAL
Vazão máxima (gpm)	6.095
Pressão de trabalho máxima - acoplado (psi)	10150

Tamanho	IMPERIAL
Tamanho da conexão (A)	3/8"
Comprimento total M+F (in)	F+D-1,00
Comprimento (in)	2,87
Diâmetro máximo (in)	1,38
Peso (lb)	0,48

Spare kits

Código de produto	Nome do produto
815700650	SPARE KIT OR NBR+BK F IV-HP38

Caps

Código de produto	Nome do produto
815603012	PLASTIC CAP F IVHP38 BLACK
815605002	STEEL CAP F IVHP38 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service