F IFR8 1/2 BSP

Codice articolo: **800200050** / **Fêmea**

Sistema de vedação Face plana non spill	**Tamanho do acoplamento** 3/8"
Vedação Nitrile NBR	**Tratamento** Cr3
Intercambiabilidade ISO 5676 "NF U 16-006"	**Sistema de conexão** Puxar o luva para trás e empurrar
Sistema de desconexão Puxar o luva para trás	**Material** Aço carbono de alta resistência
Mecanismo de trava Esfera de bloqueio	**Desconexão sob pressão** Não
Rosca FEMALE THREAD BSPP (ISO 1179-1)	**Conexão com pressão residual** Não
Temperatura -20 / +100 °C; -4 / +212 °F	**Aplicações** Máquinas agrícolas, Implementos agrícolas, Agricultura

Desempenho	IMPERIAL
ISO DN (mm)	6.3
Vazão máxima (gpm)	12.19
Pressão de trabalho máxima - acoplado (psi)	2175
Pressão de trabalho - desacoplado (psi)	2175
Pressão de ruptura - acoplado (psi)	14500
Pressão de ruptura - desacoplado (psi)	4350
Força de conexão (lbf)	38.25
Força de desconexão (lbf)	6.075
Vazamento (ml)	0.06

Tamanho	IMPERIAL
Tamanho da conexão (A)	G 1/2"
Comprimento total M+F (in)	F+D-0,59
Comprimento (in)	2,33
Diâmetro máximo (in)	1,73
Peso (lb)	0,94

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service