

F IC9R 3/8 BSP

Codice articolo: **813500208** / **Muffe**





Dichtungssystem Flat Face	**Größe** 3/8"
Dichtung EPDM	**Oberflächenschutz** Ossidazione dura
Austausch Profilo Stucchi IC	**Verbindungssystem** Drücken
Betätigungsart Druckhülse	**Werkstoff** Alluminio
Verriegelungsmechanismus Verschlusskugel	**Druckentlastende Trennung** Nein
Gewinde FEMALE THREAD BSPP (ISO 1179-1)	**Anschluss mit Restdruck** Nein
Temperatur -40 / +150 °C; -40 / +302 °F	**Anwendung** Rechenzentrum, Bahn, Windkraft, Medizintechnik, Sonstige, Digitale Sender, Elektrofahrzeuge, HVAC/R, Laser, Verteidigung, Halbleiter

Performance	METRIC
Maximaler Betriebsdruck - gekoppelt (MPa)	2
Betriebsdruck - entkoppelt (MPa)	2
Platzerdruck - gekoppelt (MPa)	8
Platzerdruck - entkoppelt (MPa)	8
Verbindungsfestigkeit (N)	92
Trennkraft (N)	24
Leckage (ml)	0.01

Größen	METRIC
Anschlussgröße (A)	3/8"
Gesamtlänge M+F (mm)	85,5
Länge (mm)	59,5
Maximaler Durchmesser (mm)	31
Gewicht (kg)	0,06

Verwandte Produkte

Produkt-code	Tipologia	Produktname
813517209	Maschio	M IC9R 3/8 BSP EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service