
M IC13RD 1/2 BSP EXT*

Codice articolo: **813517219** / **Stecker**



Dichtungssystem Flat Face	**Größe** 1/2"
Dichtung EPDM	**Oberflächenschutz** Ossidazione dura
Austausch Profilo Stucchi IC	**Verbindungssystem** Drücken
Betätigungsart Druckhülse	**Werkstoff** Alluminio
Verriegelungsmechanismus Verschlusskugel	**Druckentlastende Trennung** Nein
Gewinde MALE THREAD BSPP (ISO 8434-6)	**Anschluss mit Restdruck** Nein
Temperatur -40 / +150 °C; -40 / +302 °F	**Anwendung** Rechenzentrum, Bahn, Windkraft, Medizintechnik, Sonstige, Digitale Sender, Elektrofahrzeuge, HVAC/R, Laser, Verteidigung, Halbleiter

Performance	IMPERIAL
Maximaler Betriebsdruck - gekoppelt (psi)	290
Betriebsdruck - entkoppelt (psi)	290
Platzerdruck - gekoppelt (psi)	1160
Platzerdruck - entkoppelt (psi)	1160
Verbindungsfestigkeit (lbf)	35,1
Trennkraft (lbf)	7,9
Leckage (ml)	0.01

Größen	IMPERIAL
Anschlussgröße (A)	1/2"
Gesamtlänge M+F (in)	4,44
Länge (in)	3,19
Maximaler Durchmesser (in)	1,16
Gewicht (lb)	0,11

Verwandte Produkte

Produkt-code	Tipologia	Produktname
813500216	Femmina	F IC13R 1/2 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service