
M IC15B 3/4 BSP EXT

Codice articolo: **813517259** / **Stecker**



Dichtungssystem Flat Face	**Größe** 5/8"
Dichtung EPDM	**Oberflächenschutz** Ossidazione dura
Austausch Profilo Stucchi IC	**Verbindungssystem** Drücken
Betätigungsart Druckhülse	**Werkstoff** Alluminio
Verriegelungsmechanismus Verschlusskugel	**Druckentlastende Trennung** Nein
Gewinde MALE THREAD BSPP (ISO 8434-6)	**Anschluss mit Restdruck** Nein
Temperatur -40 / +150 °C; -40 / +302 °F	**Anwendung** Rechenzentrum, Bahn, Windkraft, Medizintechnik, Sonstige, Digitale Sender, Elektrofahrzeuge, HVAC/R, Laser, Verteidigung, Halbleiter

Performance	METRIC
Maximaler Betriebsdruck - gekoppelt (MPa)	2
Betriebsdruck - entkoppelt (MPa)	2
Platzerdruck - gekoppelt (MPa)	8
Platzerdruck - entkoppelt (MPa)	8
Verbindungsfestigkeit (N)	139
Trennkraft (N)	47
Leckage (ml)	0,01

Größen	METRIC
Anschlussgröße (A)	3/4"
Gesamtlänge M+F (mm)	135,7
Länge (mm)	81,5
Maximaler Durchmesser (mm)	33,5
Gewicht (kg)	0,08

Verwandte Produkte

Produkt-code	Tipologia	Produktname
813500258	Femmina	F IC15B 3/4 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service