F ICX7R 1/4 BSP

Codice articolo: **813600200** / **Muffe**

Dichtungssystem Flat Face	**Größe** 07
Dichtung EPDM	**Austausch** Profilo Stucchi IC
Verbindungssystem Drücken	**Betätigungsart** Druckhülse
Werkstoff Edelstahl-Innenbauteile (AISI 316L)	**Verriegelungsmechanismus** Verschlusskugel
Druckentlastende Trennung Nein	**Gewinde** FEMALE THREAD BSPP (ISO 1179-1)
Anschluss mit Restdruck Nein	**Temperatur** -40 / +150 °C; -40 / +302 °F
Anwendung Rechenzentrum, Bahn, Windkraft, Medizintechnik, Sonstige, Digitale Sender, Elektrofahrzeuge, HVAC/R, Laser, Verteidigung, Halbleiter	

Performance	IMPERIAL
Maximaler Betriebsdruck - gekoppelt (psi)	580
Betriebsdruck - entkoppelt (psi)	580
Platzerdruck - gekoppelt (psi)	2320
Platzerdruck - entkoppelt (psi)	2320
Verbindungsfestigkeit (lbf)	92
Trennkraft (lbf)	4,3
Leckage (ml)	0

Größen	IMPERIAL
Anschlussgröße (A)	1/4”
Gesamtlänge M+F (in)	3,03
Länge (in)	2,15
Maximaler Durchmesser (in)	1,02
Gewicht (lb)	0,22

Verwandte Produkte

Produkt-code	Tipologia	Produktname
813617201	Maschio	M ICX7R 1/4 BSP EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service