F ICX9B 3/8 BSP

Codice articolo: **813600242** / **Muffe**

Dichtungssystem Flat Face	**Größe** 09
Dichtung EPDM	**Austausch** Profilo Stucchi IC
Verbindungssystem Drücken	**Betätigungsart** Druckhülse
Werkstoff Edelstahl-Innenbauteile (AISI 316L)	**Verriegelungsmechanismus** Verschlusskugel
Druckentlastende Trennung Nein	**Gewinde** FEMALE THREAD BSPP (ISO 1179-1)
Anschluss mit Restdruck Nein	**Temperatur** -40 / +150 °C; -40 / +302 °F
Anwendung Rechenzentrum, Bahn, Windkraft, Medizintechnik, Sonstige, Digitale Sender, Elektrofahrzeuge, HVAC/R, Laser, Verteidigung, Halbleiter	

Performance	METRIC
Maximaler Betriebsdruck - gekoppelt (MPa)	2
Betriebsdruck - entkoppelt (MPa)	2
Platzerdruck - gekoppelt (MPa)	8
Platzerdruck - entkoppelt (MPa)	8
Verbindungsfestigkeit (N)	92
Trennkraft (N)	24
Leckage (ml)	0.01

Größen	METRIC
Anschlussgröße (A)	3/8"
Gesamtlänge M+F (mm)	85,5
Länge (mm)	59,5
Maximaler Durchmesser (mm)	31
Gewicht (kg)	0,18

Verwandte Produkte

Produkt-code	Tipologia	Produktname
813617243	Maschio	M ICX9B 3/8 BSP EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service