M IFR8 1/2 BSP EXT

Codice articolo: **800200051** / **Stecker**

Dichtungssystem Non spill flat face	**Größe** 3/8"
Dichtung Nitrile NBR	**Oberflächenschutz** Cr3
Austausch ISO 5676 "NF U 16-006"	**Verbindungssystem** Einfachwirkende Hülse und Drücken
Betätigungsart Druckhülse	**Werkstoff** Automatenstahl
Verriegelungsmechanismus Verschlusskugel	**Druckentlastende Trennung** Nein
Gewinde MALE THREAD BSPP (DIN3852/A)	**Anschluss mit Restdruck** Nein
Temperatur -20 / +100 °C; -4 / +212 °F	**Anwendung** Landmaschinen, Landwirtschaftliche Anbaugeräte, Landwirtschaft

Performance	METRIC
ISO DN (mm)	6.3
Maximaler Durchfluss (l/min)	46
Maximaler Betriebsdruck - gekoppelt (MPa)	15
Betriebsdruck - entkoppelt (MPa)	15
Platzerdruck - gekoppelt (MPa)	100
Platzerdruck - entkoppelt (MPa)	80
Verbindungsfestigkeit (N)	170
Trennkraft (N)	27
Leckage (ml)	0.06

Größen	METRIC
Anschlussgröße (A)	G 1/2"
Gesamtlänge M+F (mm)	F+D-15
Länge (mm)	49,1
Maximaler Durchmesser (mm)	35
Gewicht (kg)	0,19

Caps

Produkt-code	Produktname
814901027	PLASTIC CAP M IFR8 YELLOW

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service