F IFR8 M18X1.5

Codice articolo: **800212000** / **Muffe**

Dichtungssystem Non spill flat face	**Größe** 3/8"
Dichtung Nitrile NBR	**Oberflächenschutz** Cr3
Austausch ISO 5676 "NF U 16-006"	**Verbindungssystem** Einfachwirkende Hülse und Drücken
Betätigungsart Druckhülse	**Werkstoff** Automatenstahl
Verriegelungsmechanismus Verschlusskugel	**Druckentlastende Trennung** Nein
Gewinde FEMALE THREAD METRIC	**Anschluss mit Restdruck** Nein
Temperatur -20 / +100 °C; -4 / +212 °F	**Anwendung** Landmaschinen, Landwirtschaftliche Anbaugeräte, Landwirtschaft

Performance	IMPERIAL
ISO DN (mm)	6.3
Maximaler Durchfluss (gpm)	12.19
Maximaler Betriebsdruck - gekoppelt (psi)	2175
Betriebsdruck - entkoppelt (psi)	2175
Platzerdruck - gekoppelt (psi)	14500
Platzerdruck - entkoppelt (psi)	4350
Verbindungsfestigkeit (lbf)	38.25
Trennkraft (lbf)	6.075
Leckage (ml)	0.06

Größen	IMPERIAL
Anschlussgröße (A)	M18x1.5
Gesamtlänge M+F (in)	F+D-0,59
Länge (in)	2,13
Maximaler Durchmesser (in)	1,73
Gewicht (lb)	0,88

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service