M A5HP 1/4 BSP*

Codice articolo: **801600001** / **Stecker** / ***Prodotto disponibile su richiesta**

Dichtungssystem Flat Face	**Größe** 1/4"
Dichtung Nitrile NBR	**Oberflächenschutz** Cr3
Austausch Stucchi Austausch A-HP	**Verbindungssystem** Drücken
Betätigungsart Druckhülse	**Werkstoff** Automatenstahl
Verriegelungsmechanismus Verschlusskugel + Sicherheitsring	**Druckentlastende Trennung** Nein
Gewinde FEMALE THREAD BSPP (ISO 1179-1)	**Anschluss mit Restdruck** Nein
Temperatur -20 / +100 °C; -4 / +212 °F	**Anwendung** Rettungsgeräte, Hydraulikaggregate, Hydraulikwerkzeuge

Performance	METRIC
Maximaler Durchfluss (l/min)	24
Maximaler Betriebsdruck - gekoppelt (MPa)	70
Betriebsdruck - entkoppelt (MPa)	70
Platzerdruck - gekoppelt (MPa)	200
Platzerdruck - entkoppelt (MPa)	200
Verbindungsfestigkeit (N)	125
Trennkraft (N)	45
Leckage (ml)	0.02

Größen	METRIC
Anschlussgröße (A)	1/4"
Gesamtlänge M+F (mm)	94,9
Länge (mm)	47,9
Maximaler Durchmesser (mm)	23,8
Gewicht (kg)	0,09

Verwandte Produkte

Produkt-code	Tipologia	Produktname
801600000	Femmina	F A5HP 1/4 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service