
# F A5HP 3/8 BSP*

Codice articolo: **801600002** / **Muffe** / ***Prodotto disponibile su richiesta**




| | |
|---|---|
| **Dichtungssystem**<br>Flat Face | **Größe**<br>1/4" |
| **Dichtung**<br>Nitrile NBR | **Oberflächenschutz**<br>Cr3 |
| **Austausch**<br>Stucchi Austausch A-HP | **Verbindungssystem**<br>Drücken |
| **Betätigungsart**<br>Druckhülse | **Werkstoff**<br>Automatenstahl |
| **Verriegelungsmechanismus**<br>Verschlusskugel + Sicherheitsring | **Druckentlastende Trennung**<br>Nein |
| **Gewinde**<br>FEMALE THREAD BSPP (ISO 1179-1) | **Anschluss mit Restdruck**<br>Nein |
| **Temperatur**<br>-20 / +100 °C; -4 / +212 °F | **Anwendung**<br>Rettungsgeräte, Hydraulikaggregate, Hydraulikwerkzeuge |

| Performance | METRIC |
|---|---|
| Maximaler Durchfluss (l/min) | 24 |
| Maximaler Betriebsdruck - gekoppelt (MPa) | 70 |
| Betriebsdruck - entkoppelt (MPa) | 50 |
| Platzerdruck - gekoppelt (MPa) | 200 |
| Platzerdruck - entkoppelt (MPa) | 150 |
| Verbindungsfestigkeit (N) | 125 |
| Trennkraft (N) | 45 |
| Leckage (ml) | 0.02 |

| Größen | METRIC |
|---|---|
| Anschlussgröße (A) | 3/8" |
| Gesamtlänge M+F (mm) | 103,9 |
| Länge (mm) | 60 |
| Maximaler Durchmesser (mm) | 29 |
| Gewicht (kg) | 0,2 |

Verwandte Produkte

| Produkt-code | Tipologia | Produktname |
|---|---|---|
| 801600003 | Maschio | M A5HP 3/8 BSP |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service