M A9HP 3/8 BSP*

Codice articolo: **801600007** / **Stecker** / ***Prodotto disponibile su richiesta**

Dichtungssystem Flat Face	**Größe** 3/8"
Dichtung Nitrile NBR	**Oberflächenschutz** Cr3
Austausch Stucchi Austausch A-HP	**Verbindungssystem** Drücken
Betätigungsart Druckhülse	**Werkstoff** Automatenstahl
Verriegelungsmechanismus Verschlusskugel + Sicherheitsring	**Druckentlastende Trennung** Nein
Gewinde FEMALE THREAD BSPP (ISO 1179-1)	**Anschluss mit Restdruck** Nein
Temperatur -20 / +100 °C; -4 / +212 °F	**Anwendung** Rettungsgeräte, Hydraulikaggregate, Hydraulikwerkzeuge

Performance	IMPERIAL
Maximaler Durchfluss (gpm)	12.19
Maximaler Betriebsdruck - gekoppelt (psi)	10150
Betriebsdruck - entkoppelt (psi)	10150
Platzerdruck - gekoppelt (psi)	26100
Platzerdruck - entkoppelt (psi)	29000
Verbindungsfestigkeit (lbf)	46.125
Trennkraft (lbf)	11.25
Leckage (ml)	0.02

Größen	IMPERIAL
Anschlussgröße (A)	3/8"
Gesamtlänge M+F (in)	4,28
Länge (in)	2,36
Maximaler Durchmesser (in)	1,14
Gewicht (lb)	0,33

Verwandte Produkte

Produkt-code	Tipologia	Produktname
801600006	Femmina	F A9HP 3/8 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service