F A9HP 1/2 BSP*

Codice articolo: **801600008 / Muffe** / ***Prodotto disponibile su richiesta**

Dichtungssystem Flat Face	**Größe** 3/8"
Dichtung Nitrile NBR	**Oberflächenschutz** Cr3
Austausch Stucchi Austausch A-HP	**Verbindungssystem** Drücken
Betätigungsart Druckhülse	**Werkstoff** Automatenstahl
Verriegelungsmechanismus Verschlusskugel + Sicherheitsring	**Druckentlastende Trennung** Nein
Gewinde FEMALE THREAD BSPP (ISO 1179-1)	**Anschluss mit Restdruck** Nein
Temperatur -20 / +100 °C; -4 / +212 °F	**Anwendung** Rettungsgeräte, Hydraulikaggregate, Hydraulikwerkzeuge

Performance	METRIC
Maximaler Durchfluss (l/min)	46
Maximaler Betriebsdruck - gekoppelt (MPa)	70
Betriebsdruck - entkoppelt (MPa)	42
Platzerdruck - gekoppelt (MPa)	180
Platzerdruck - entkoppelt (MPa)	125
Verbindungsfestigkeit (N)	205
Trennkraft (N)	50
Leckage (ml)	0.02

Größen	METRIC
Anschlussgröße (A)	1/2"
Gesamtlänge M+F (mm)	116,3
Länge (mm)	69,6
Maximaler Durchmesser (mm)	34
Gewicht (kg)	0,3

Verwandte Produkte

Produkt-code	Tipologia	Produktname
801600009	Maschio	M A9HP 1/2 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service