
M A5HP 3/8 NPT

Codice articolo: **801601009** / **Stecker**



Dichtungssystem Flat Face	**Größe** 1/4"
Dichtung Nitrile NBR	**Oberflächenschutz** Cr3
Austausch Stucchi Austausch A-HP	**Verbindungssystem** Drücken
Betätigungsart Druckhülse	**Werkstoff** Automatenstahl
Verriegelungsmechanismus Verschlusskugel + Sicherheitsring	**Druckentlastende Trennung** Nein
Gewinde FEMALE THREAD NPT (ANSI B.1.20.1)	**Anschluss mit Restdruck** Nein
Temperatur -20 / +100 °C; -4 / +212 °F	**Anwendung** Rettungsgeräte, Hydraulikaggregate, Hydraulikwerkzeuge

Performance	IMPERIAL
Maximaler Durchfluss (gpm)	6.36
Maximaler Betriebsdruck - gekoppelt (psi)	10150
Betriebsdruck - entkoppelt (psi)	10150
Platzerdruck - gekoppelt (psi)	29000
Platzerdruck - entkoppelt (psi)	29000
Verbindungsfestigkeit (lbf)	28.125
Trennkraft (lbf)	10.125
Leckage (ml)	0.02

Größen	IMPERIAL
Anschlussgröße (A)	3/8"
Gesamtlänge M+F (in)	4,09
Länge (in)	2,16
Maximaler Durchmesser (in)	0,65
Gewicht (lb)	0,24

Verwandte Produkte

Produkt-code	Tipologia	Produktname
801601008	Femmina	F A5HP 3/8 NPT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service