# M I12GS 1/2 SAE EXT*

Codice articolo: **809404001** / **Stecker** / ***Prodotto disponibile su richiesta**

Stucchi®

| | |
|---|---|
| **Dichtungssystem**<br>Schnellverschlusskupplungen | **Größe**<br>1/2" |
| **Dichtung**<br>Nitrile NBR | **Oberflächenschutz**<br>Cr3 |
| **Austausch**<br>ISO 7241 A | **Verbindungssystem**<br>Drücken |
| **Betätigungsart**<br>Ziehen | **Werkstoff**<br>Automatenstahl |
| **Verriegelungsmechanismus**<br>Verschlusskugel | **Druckentlastende Trennung**<br>Nein |
| **Gewinde**<br>MALE THREAD SAE (ISO 11926-2 & SAE J514) | **Anschluss mit Restdruck**<br>Nein |
| **Temperatur**<br>-20 / +100 °C; -4 / +212 °F | **Anwendung**<br>Landmaschinen, Landwirtschaftliche Anbaugeräte, Landwirtschaft |

| Performance | IMPERIAL |
|---|---|
| ISO DN (mm) | 12.5 |
| Maximaler Durchfluss (gpm) | 23.85 |
| Maximaler Betriebsdruck - gekoppelt (psi) | 3625 |
| Betriebsdruck - entkoppelt (psi) | 3625 |
| Platzerdruck - gekoppelt (psi) | 13050 |
| Platzerdruck - entkoppelt (psi) | 14500 |
| Verbindungsfestigkeit (lbf) | 20,25 |
| Trennkraft (lbf) | 18 |
| Leckage (ml) | 1.8 |

| Größen | IMPERIAL |
|---|---|
| Anschlussgröße (A) | 3/4-16UNF |
| Gesamtlänge M+F (in) | 4,24 |
| Länge (in) | 2,39 |
| Maximaler Durchmesser (in) | 1,18 |
| Gewicht (lb) | 0,31 |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service