Stucchi®

Experts in quick couplings since 1960



For over 60 years, Stucchi is one of the leading manufacturers of quick disconnect couplings.

With a wide variety of sizes and port configurations ranging from 1/8" to 2" suitable for some of the most demanding applications.

To compliment our core product we offer the FCP range which includes swivels, suregrips, check, ball and flow control valves.

Our solutions-based approach meets the demanding requirements for applications across multiple markets.



EUROPEAN STUCCHI QUALITY

INSIST ON THE BRAND

SJ SERIES



Available Size: **From DN6 to DN50**
Operating pressure: **Up to 400 bar**
Ends: **BSP - NPT**
Material/treatment: **316L, Carbon Steel**
Connection system: **Screw**
Profile: **Straight & 90 degree**

IRBX SERIES



Valving style: **Poppet**
Interchange: **ISO 7241 'B'**
Sealing description: **FKM (Viton®)**
Available sizes: **From 1/8" to 1"**
Operating pressure: **Up to 250 bar**
Flow rate: **Up to 200 l/min**
Material / Treatment: **316L**

VUX SERIES



Available Sizes: **From 1/8" to 2"**
Operating Pressure: **Up to 400 bar**
Flow rate: **Up to 1000 L/min**
Material / Treatment: **316L**

SOLUTIONS

STAINLESS

Dandenong South, Victoria Ph: +61 3 9793 4611
Malaga, Western Australia Ph: +61 8 6365 4868
Brendale, Queensland Ph: +61 7 3495 0222
East Tamaki, New Zealand Ph: +64 800 005 905 | info@stucchinz.com | stucchinz.com
info@stucchiaustralia.com | stucchiaustralia.com

Stucchi® | FCP


Stucchi®

Experts in quick couplings since 1960

BALL VALVES


COUPLINGS

FE2 SERIES



Number of Ports: **2**
Material: **Available in carbon steel and stainless steel**
Available Sizes: **¼ to 1”**
Port: **NPT, BSP, SAE, Flange**
Operating Pressure: **Up to 500 bar**
Temperature range: **-60 + 230 °C (dependent on body and seal material)**

FE3 SERIES



Number of Ports: **3**
Port Type: **L and T**
Material: **Available in carbon steel and stainless**
Available Sizes: **¼ to 1”**
Port: **NPT, BSP**
Operating Pressure: **Up to 400 bar**
Temperature range: **-60 + 230 °C (dependent on body and seal material)**

20 SERIES



Valving style: **Poppet**
Interchange: **ISO 7241-1 A**
Available sizes: **From 1/4” to 2”**
Operating pressure: **Up to 350 bar**
Flow rate: **Up to 1000 L/Min**
Material: **316L**
Connection system: **Single acting sleeve**
Connection under pressure: **Not allowed**

30 SERIES



Valving style: **Poppet**
Interchange: **ISO 14541**
Available sizes: **From 1/4” to 1 1/4”**
Operating pressure: **Up to 450 bar**
Flow rate: **Up to 378 L/Min**
Material: **316L**
Connection system: **Screw**
Connection under pressure: **One side**

40 SERIES



Valving style: **Poppet**
Interchange: **VVS Interchange**
Available Sizes: **From 1/4” to 2”**
Operating Pressure: **Up to 650 bar**
Flow rate: **Up to 750 L/min**
Material: **316L**
Connection system: **Screw**
Connection under pressure: **One side**

IRCX SERIES



Valving style: **Poppet**
Interchange: **Nordic interface**
Sealing description: **FKM (Viton®)**
Available sizes: **From 1/4” to 1”**
Operating pressure: **Up to 300 bar**
Flow rate: **Up to 378 l/min**
Material / Treatment: **316L**

FL SERIES



Valving style: **Flat face**
Interchange: **ISO 16028**
Sealing description: **FKM (Viton®)**
Available sizes: **From 1/8” to 2”**
Operating pressure: **Up to 350 bar**
Flow rate: **Up to 1000 l/min**
Material / Treatment: **316L**

VOFX SERIES



Valving style: **Poppet**
Interchange: **With similar couplings**
Sealing description: **Nitrile NBR**
Available sizes: **From 3/4” to 2”**
Operating pressure: **Up to 207 bar**
Flow rate: **Up to 1100 l/min**
Material / Treatment: **316L**
Connection under pressure: **Allowed**

Dandenong South, Victoria Ph: +61 3 9793 4611
Malaga, Western Australia Ph: +61 8 6365 4868
Brendale, Queensland Ph: +61 7 3495 0222
East Tamaki, New Zealand Ph: +64 800 005 905 | info@stucchinz.com | stucchinz.com
info@stucchiaustralia.com | stucchiaustralia.com

Stucchi® | FCP