F IC9RV 3/8 BSP

Codice articolo: **813500108** / **Female**

Valving style Flat face	**Body size** 3/8"
Sealing FKM (VITON)	**Treatment** Ossidazione dura
Interchange Profilo Stucchi IC	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Alluminio
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -15 / +150 °C; +5 / +302 °F	**Applications** Data Center, Rail, Windmill, Medical Devices, Others, Digital Transmitters, Electric Vehicles, HVAC/R, Laser, Defence, Semiconductors

Performance	METRIC
Max. Operating pressure - coupled (MPa)	2
Operating pressure - uncoupled (MPa)	2
Burst pressure - coupled (MPa)	8
Burst pressure - uncoupled (MPa)	8
Connect force (N)	92
Disconnect force (N)	24
Spillage (ml)	0.01

Dimensions	METRIC
Port (A)	3/8"
Overall length M+F (mm)	85,5
Length (mm)	59,5
Max. diameter (mm)	31
Weight (kg)	0,06

Related products

Item code	Type	Product name
813517109	Maschio	M IC9RV 3/8 BSP EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service