F IC15RV 3/4 BSP

Codice articolo: **813500124** / **Female**

Valving style Flat face	**Body size** 5/8"
Sealing FKM (VITON)	**Treatment** Ossidazione dura
Interchange Profilo Stucchi IC	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Alluminio
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -15 / +150 °C; +5 / +302 °F	**Applications** Data Center, Rail, Windmill, Medical Devices, Others, Digital Transmitters, Electric Vehicles, HVAC/R, Laser, Defence, Semiconductors

Performance	IMPERIAL
Max. Operating pressure - coupled (psi)	290
Operating pressure - uncoupled (psi)	290
Burst pressure - coupled (psi)	1160
Burst pressure - uncoupled (psi)	1160
Connect force (lbf)	31,3
Disconnect force (lbf)	10,6
Spillage (ml)	0,01

Dimensions	IMPERIAL
Port (A)	3/4"
Overall length M+F (in)	5,34
Length (in)	3,9
Max. diameter (in)	1,63
Weight (lb)	0,42

Related products

Item code	Type	Product name
813517125	Maschio	M IC15RV 3/4 BSP EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service