M IC13RV 1/2 BSP EXT

Codice articolo: **813517117** / **Male**

Valving style Flat face	**Body size** 1/2"
Sealing FKM (VITON)	**Treatment** Ossidazione dura
Interchange Profilo Stucchi IC	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Alluminio
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread MALE THREAD BSPP (ISO 8434-6)	**Connectable under residual pressure** No
Temperature -15 / +150 °C; +5 / +302 °F	**Applications** Data Center, Rail, Windmill, Medical Devices, Others, Digital Transmitters, Electric Vehicles, HVAC/R, Laser, Defence, Semiconductors

Performance	METRIC
Max. Operating pressure - coupled (MPa)	2
Operating pressure - uncoupled (MPa)	2
Burst pressure - coupled (MPa)	8
Burst pressure - uncoupled (MPa)	8
Connect force (N)	156
Disconnect force (N)	35
Spillage (ml)	0.01

Dimensions	METRIC
Port (A)	1/2"
Overall length M+F (mm)	112,8
Length (mm)	70,5
Max. diameter (mm)	29,5
Weight (kg)	0,05

Related products

Item code	Type	Product name
813500116	Femmina	F IC13RV 1/2 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service