
F IR34 BSP

Codice articolo: **800000006** / **Female**



Valving style Ball	**Body size** 3/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Similar couplings (IR)	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	IMPERIAL
Max. Flow suggested (gpm)	39.22
Max. Operating pressure - coupled (psi)	3625
Operating pressure - uncoupled (psi)	3625
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	13050
Connect force (lbf)	42.75
Disconnect force (lbf)	10.125
Spillage (ml)	4.5

Dimensions	IMPERIAL
Port (A)	3/4"
Overall length M+F (in)	4,66
Length (in)	3,56
Max. diameter (in)	1,89
Weight (lb)	1,5

Related products

Item code	Type	Product name
800000007	Maschio	M IR34 BSP

Spare kits

Item code	Product name
815700354	SPARE KIT OR NBR F IR34

Caps

Item code	Product name
815000006	PLASTIC PLUG F ISO-A/IR34 RED

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service