F IR100 BSP

Codice articolo: **800000008** / **Female**

Valving style Ball	**Body size** 1"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Similar couplings (IR)	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	METRIC
Max. Flow suggested (l/min)	150
Max. Operating pressure - coupled (MPa)	20
Operating pressure - uncoupled (MPa)	20
Burst pressure - coupled (MPa)	80
Burst pressure - uncoupled (MPa)	80
Connect force (N)	100
Disconnect force (N)	45
Spillage (ml)	6

Dimensions	METRIC
Port (A)	1"
Overall length M+F (mm)	132,8
Length (mm)	99,6
Max. diameter (mm)	54
Weight (kg)	0,87

Related products

Item code	Type	Product name
800000009	Maschio	M IR100 BSP

Spare kits

Item code	Product name
815700356	SPARE KIT OR NBR F IR100

Caps

Item code	Product name
815000008	PLASTIC PLUG F ISO-A/IR100 RED

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service