
F IR14 NPT

Codice articolo: **800001000** / **Female**



Valving style Ball	**Body size** 1/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Similar couplings (IR)	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD NPT (ANSI B.1.20.1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	IMPERIAL
Max. Flow suggested (gpm)	5.3
Max. Operating pressure - coupled (psi)	4350
Operating pressure - uncoupled (psi)	4350
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	11.25
Disconnect force (lbf)	10.125
Spillage (ml)	0.13

Dimensions	IMPERIAL
Port (A)	1/4"
Overall length M+F (in)	2,54
Length (in)	1,93
Max. diameter (in)	1,06
Weight (lb)	0,25

Related products

Item code	Type	Product name
800001001	Maschio	M IR14 NPT

Spare kits

Item code	Product name
815700348	SPARE KIT OR NBR F IR14

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service