
M IR14 NPT

Codice articolo: **800001001** / **Male**



Valving style Ball	**Body size** 1/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Similar couplings (IR)	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD NPT (ANSI B.1.20.1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	METRIC
Max. Flow suggested (l/min)	20
Max. Operating pressure - coupled (MPa)	30
Operating pressure - uncoupled (MPa)	30
Burst pressure - coupled (MPa)	100
Burst pressure - uncoupled (MPa)	100
Connect force (N)	50
Disconnect force (N)	45
Spillage (ml)	0.13

Dimensions	METRIC
Port (A)	1/4"
Overall length M+F (mm)	64,4
Length (mm)	32,5
Max. diameter (mm)	14,2
Weight (kg)	0,04

Related products

Item code	Type	Product name
800001000	Femmina	F IR14 NPT

Caps

Item code	Product name
815001001	PLASTIC CAP M IR14 YELLOW*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service