
M IR14V NPT

Codice articolo: **800101001** / **Male**



Valving style Poppet	**Body size** 1/4"
Sealing FKM (VITON)	**Treatment** Cr3
Interchange Similar couplings (IR-V)	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD NPT (ANSI B.1.20.1)	**Connectable under residual pressure** No
Temperature -15 / +180 °C; +5 / +356 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	IMPERIAL
Max. Flow suggested (gpm)	6.36
Max. Operating pressure - coupled (psi)	4350
Operating pressure - uncoupled (psi)	4350
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	18
Disconnect force (lbf)	9
Spillage (ml)	0.33

Dimensions	IMPERIAL
Port (A)	1/4"
Overall length M+F (in)	2,59
Length (in)	1,28
Max. diameter (in)	0,56
Weight (lb)	0,09

Related products

Item code	Type	Product name
800101000	Femmina	F IR14V NPT

Caps

Item code	Product name
815000001	PLASTIC CAP M ISO-A/IR14 RED
815001001	PLASTIC CAP M IR14 YELLOW*
815002001	PLASTIC CAP M IR14 BLUE*
815003001	PLASTIC CAP M IR14 BLACK*
815004001	PLASTIC CAP M IR14 GREEN*
815005001	PLASTIC CAP M IR14 WHITE*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service