
# F IV38HP 3/8 NPT EXT

Codice articolo: **800201004** / **Female**







| | |
|---|---|
| **Valving style**<br>Ball | **Body size**<br>3/8" |
| **Sealing**<br>Nitrile NBR | **Treatment**<br>Cr3 |
| **Interchange**<br>ISO14540 (High pressure) | **Connection system**<br>Screw |
| **Disconnection system**<br>Unscrew | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Screw to connect | **Disconnectable under pressure**<br>No |
| **Thread**<br>MALE THREAD NPT (ANSI B1.20.1) | **Connectable under residual pressure**<br>No |
| **Temperature**<br>-20 / +100 °C; -4 / +212 °F | **Applications**<br>Rescue Equipment, Hydraulic Tools |

| Performance | IMPERIAL |
|---|---|
| Max. Flow suggested (gpm) | 6.095 |
| Max. Operating pressure - coupled (psi) | 10150 |

| Dimensions | IMPERIAL |
|---|---|
| Port (A) | 3/8" |
| Overall length M+F (in) | F+D-1,00 |
| Length (in) | 2,84 |
| Max. diameter (in) | 1,38 |
| Weight (lb) | 0,49 |

## Spare kits

| Item code | Product name |
|---|---|
| 815700650 | SPARE KIT OR NBR+BK F IV-HP38 |

## Caps

| Item code | Product name |
|---|---|
| 815603012 | PLASTIC CAP F IVHP38 BLACK |
| 815605002 | STEEL CAP F IVHP38 NATURAL |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service