M IFR8 M20X1.5 EXT

Codice articolo: **800215003** / **Male**

Valving style Flat face non spill	**Body size** 3/8"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 5676 "NF U 16-006"	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread MALE THREAD METRIC L - 24° CONE (ISO 8434-1 & DIN 2353)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	IMPERIAL
ISO DN (mm)	6.3
Max. Flow suggested (gpm)	12.19
Max. Operating pressure - coupled (psi)	2175
Operating pressure - uncoupled (psi)	2175
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	11600
Connect force (lbf)	38.25
Disconnect force (lbf)	6.075
Spillage (ml)	0.06

Dimensions	IMPERIAL
Port (A)	M20X1.5
Overall length M+F (in)	F+D-0,59
Length (in)	2,29
Max. diameter (in)	1,38
Weight (lb)	0,44

Caps

Item code	Product name
814901027	PLASTIC CAP M IFR8 YELLOW

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service