

Body size 3/8"	Valving style Poppet
Interchange ISO 7241 A	Sealing Nitrile NBR
Connection system Pull back the sleeve and push	Disconnection system Pull back the sleeve
Material Carbon steel	Treatment Cr3
Locking mechanism Locking ball	Disconnectable under pressure No
Thread FEMALE THREAD BSPP (ISO 1179-1)	Connectable under residual pressure No
Temperature -20 / +100 °C; -4 / +212 °F	Applications Agriculture, Industry

Performance	METRIC	Dimensions	METRIC
ISO DN (mm)	10	Port (A)	3/8"
Flow (l/min)	Da 20 a 50	Overall length M+F (mm)	76,8
Max. Flow suggested (l/min)	46	Length (mm)	38
Max. Operating pressure - coupled (Mpa)	30	Max. diameter (mm)	24
Operating pressure - uncoupled (mpa)	30	Weight (kg)	0,05
Burst pressure - coupled (mpa)	100		
Burst pressure - uncoupled (mpa)	100		
Connect force (N)	90		
Disconnect force (N)	30		
Spillage (ml)	1.2		

Related products

Item code	Type	Product name
800503002	Femmina	F BIR38 BSPT

Caps

Item code	Product name
815001015	PLASTIC CAP M ISO-A 38 YELLOW**

**Product available upon request