
# F A9 1/2 BSP EXT

Codice articolo: **801300012** / **Female**




| | |
|---|---|
| **Valving style**<br>Flat face | **Body size**<br>3/8" |
| **Sealing**<br>Nitrile NBR | **Treatment**<br>Cr3 |
| **Interchange**<br>ISO 16028 | **Connection system**<br>Push |
| **Disconnection system**<br>Pull back the sleeve | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Locking ball + Safety lock | **Disconnectable under pressure**<br>No |
| **Thread**<br>MALE THREAD BSPP (ISO 8434-6) | **Connectable under residual pressure**<br>No |
| **Temperature**<br>-20 / +100 °C; -4 / +212 °F | **Applications**<br>Material Handling, Robotics & Automation, Paper, Packaging, Leather, Hydraulic Tools, Hydraulic Power Units, Injection Moulding, Die Casting, Others, Test Bench, Steel Mill, Rail, Road Construction, Foundation, Earth Moving, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Ceramic, Agricultural Attachments, Agricultural Machinery, Earthmoving, Agriculture, Vehicles, Oil & Gas |

| Performance | IMPERIAL |
|---|---|
| ISO DN (mm) | 10 |
| Max. Flow suggested (gpm) | 12.19 |
| Max. Operating pressure - coupled (psi) | 5075 |
| Operating pressure - uncoupled (psi) | 5075 |
| Burst pressure - coupled (psi) | 14500 |
| Burst pressure - uncoupled (psi) | 14500 |
| Connect force (lbf) | 38.25 |
| Disconnect force (lbf) | 9 |
| Spillage (ml) | 0.01 |

| Dimensions | IMPERIAL |
|---|---|
| Port (A) | 1/2" |
| Overall length M+F (in) | 4,83 |
| Length (in) | 2,8 |
| Max. diameter (in) | 1,26 |
| Weight (lb) | 0,6 |

## Related products

| Item code | Type | Product name |
|---|---|---|
| 801300011 | Maschio | M A9 1/2 BSP EXT |

## Caps

| Item code | Product name |
|---|---|
| 815100002 | PLASTIC CAP F FF38 RED |
| 815200002 | PLASTIC FLIP CAP F FF38 RED |
| 816005004 | ALUMINUM CAP F FF38 NATURAL |
| 815101002 | PLASTIC CAP F FF38 YELLOW* |
| 815102002 | PLASTIC CAP F FF38 BLUE* |
| 815103002 | PLASTIC CAP F FF38 BLACK* |
| 815104002 | PLASTIC CAP F FF38 GREEN* |
| 815107002 | PLASTIC CAP F FF38 ORANGE* |
| 815110002 | PLASTIC CAP F FF38 MAGENTA* |
| 815201002 | PLASTIC FLIP CAP F FF38 YELLOW* |
| 815202002 | PLASTIC FLIP CAP F FF38 BLUE* |
| 815203002 | PLASTIC FLIP CAP F FF38 BLACK* |
| 815204002 | PLASTIC FLIP CAP F FF38 GREEN* |

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service