M A5HP 1/4 BSP*

Codice articolo: **801600001** / **Male** / ***Prodotto disponibile su richiesta**

Valving style Flat face	**Body size** 1/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Stucchi profile A-HP	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety sleeve	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Rescue Equipment, Hydraulic Power Units, Hydraulic Tools

Performance	IMPERIAL
Max. Flow suggested (gpm)	6.36
Max. Operating pressure - coupled (psi)	10150
Operating pressure - uncoupled (psi)	10150
Burst pressure - coupled (psi)	29000
Burst pressure - uncoupled (psi)	29000
Connect force (lbf)	28.125
Disconnect force (lbf)	10.125
Spillage (ml)	0.02

Dimensions	IMPERIAL
Port (A)	1/4"
Overall length M+F (in)	3,74
Length (in)	1,89
Max. diameter (in)	0,94
Weight (lb)	0,19

Related products

Item code	Type	Product name
801600000	Femmina	F A5HP 1/4 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service