
F A4HP 1/8 BSP*

Codice articolo: **801600010** / **Female** / ***Prodotto disponibile su richiesta**



Valving style Flat face	**Body size** 1/8"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Stucchi profile A-HP	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety sleeve	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Rescue Equipment, Hydraulic Power Units, Hydraulic Tools

Performance	METRIC
Max. Flow suggested (l/min)	6
Max. Operating pressure - coupled (MPa)	70
Operating pressure - uncoupled (MPa)	70
Burst pressure - coupled (MPa)	160
Burst pressure - uncoupled (MPa)	160
Connect force (N)	95
Disconnect force (N)	40
Spillage (ml)	0.04

Dimensions	METRIC
Port (A)	1/8"
Overall length M+F (mm)	72,3
Length (mm)	44
Max. diameter (mm)	22
Weight (kg)	0,09

Related products

Item code	Type	Product name
801600011	Maschio	M A4HP 1/8 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service