
F FL9N 3/8 BSP*

Codice articolo: **802400002** / **Female** / ***Prodotto disponibile su richiesta**



Valving style Flat face	**Body size** 3/8"
Sealing Nitrile NBR	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -20 / +100 °C; -4 / +212 °F

Applications
Medical Devices, Semiconductors, Packaging, Food & Beverage, Laser, Electric Vehicles, Digital Transmitters, Injection Moulding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	10
Max. Flow suggested (gpm)	12.19
Max. Operating pressure - coupled (psi)	5075
Operating pressure - uncoupled (psi)	2175
Burst pressure - coupled (psi)	20300
Burst pressure - uncoupled (psi)	8700
Connect force (lbf)	36
Disconnect force (lbf)	10.125
Spillage (ml)	0.01

Dimensions	IMPERIAL
Port (A)	3/8"
Overall length M+F (in)	4,28
Length (in)	2,53
Max. diameter (in)	1,26
Weight (lb)	0,55

Related products

Item code	Type	Product name
802400003	Maschio	M FL9N 3/8 BSP

Caps

Item code	Product name
815100002	PLASTIC CAP F FF38 RED
815200002	PLASTIC FLIP CAP F FF38 RED
816005004	ALUMINUM CAP F FF38 NATURAL
815101002	PLASTIC CAP F FF38 YELLOW**
815102002	PLASTIC CAP F FF38 BLUE**
815103002	PLASTIC CAP F FF38 BLACK**
815104002	PLASTIC CAP F FF38 GREEN**
815107002	PLASTIC CAP F FF38 ORANGE**
815110002	PLASTIC CAP F FF38 MAGENTA**
815201002	PLASTIC FLIP CAP F FF38 YELLOW**
815202002	PLASTIC FLIP CAP F FF38 BLUE**
815203002	PLASTIC FLIP CAP F FF38 BLACK**
815204002	PLASTIC FLIP CAP F FF38 GREEN**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service