







Body size 1/4"	Valving style Poppet
Interchange	Sealing
ISO 7241 B	FKM (VITON)
Connection system Pull back the sleeve and push	Disconnection system Pull back the sleeve
Material	Locking mechanism
Stainless steel (AISI 316L) + Retainer in Brass	Locking ball
Disconnectable under pressure	Thread
No	FEMALE THREAD NPT (ANSI B.1.20.1)
Connectable under residual pressure	Temperature
No	-15 / +180 °C; +5 / +356 °F
Applications Oil & Gas, Industry, Cooling, Chemical & Food industry	

Performance	IMPERIAL	
ISO DN (mm)	6.3	
Flow (gpm)	From 5,3 to 13,25	
Max. Flow suggested (gpm)	6.36	
Max. Operating pressure - coupled (psi)	3625	
Operating pressure - uncoupled (psi)	3625	
Burst pressure - coupled (psi)	20300	
Burst pressure - uncoupled (psi)	20300	
Connect force (lbf)	13.5	
Disconnect force (lbf)	6.75	
Spillage (ml)	0.33	

Dimensions	IMPERIAL
Port (A)	1/4"
Overall length M+F (in)	2,78
Length (in)	1,38
Max. diameter (in)	0,56
Weight (lb)	0,08

Related products

Item code	Туре	Product name
804601102	Femmina	F IRBX14 NPT

Caps

Item code	Product name	
815000033	PLASTIC CAP M ISO-B 14 RED	
815003033	PLASTIC CAP M ISO-B 14 BLACK*	

^{*}Product available upon request