
M VEP9P 1/2 BSP

Codice articolo: **807200005** / **Male**



Valving style Flat face	**Body size** 3/8"
Sealing Nitrile NBR	**Treatment** Cr3 + QPQ
Interchange Stucchi profile VEP	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** Yes
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** Pressure in both sides
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Steel Mill, Die Casting, Hydraulic Tools, Earthmoving, Vehicles, Oil & Gas

Performance	METRIC
Max. Flow suggested (l/min)	46
Max. Operating pressure - coupled (MPa)	55
Operating pressure - uncoupled (MPa)	55
Burst pressure - coupled (MPa)	140
Burst pressure - uncoupled (MPa)	140
Spillage (ml)	0.04
Manual connect torque (Nm)	2.2
Manual disconnect torque (Nm)	1.4
Tightening torque (Nm)	56-60

Dimensions	METRIC
Port (A)	1/2"
Overall length M+F (mm)	138,8
Length (mm)	85
Max. diameter (mm)	37,8
Weight (kg)	0,32

Related products

Item code	Type	Product name
807200004	Femmina	F VEP9P 1/2 BSP

Spare kits

Item code	Product name
815700736	SPARE KIT OR NBR+BK M VEP9

Caps

Item code	Product name
815305073	ALUMINUM CAP M VEP9 NATURAL
815300073	ALUMINUM CAP M VEP9 RED*
815301073	ALUMINUM CAP M VEP9 YELLOW*
815302073	ALUMINUM CAP M VEP9 BLUE*
815303073	ALUMINUM CAP M VEP9 BLACK*
815304073	ALUMINUM CAP M VEP9 GREEN*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service