
F A9HD BC6.5/15.6 3/8 BSP*

Codice articolo: **808300032** / **Female** / ***Prodotto disponibile su richiesta**



Valving style Flat face	**Body size** 3/8"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 16028	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety lock	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** Pressure in male side only
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Foundation, Paper, Packaging, Leather, Hydraulic Tools, Hydraulic Power Units, Others, Road Construction, Material Handling, Earth Moving, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Ceramic, Earthmoving, Vehicles, Oil & Gas

Performance	IMPERIAL
ISO DN (mm)	10
Max. Flow suggested (gpm)	12.19
Max. Operating pressure - coupled (psi)	5075
Operating pressure - uncoupled (psi)	5075
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	42.75
Disconnect force (lbf)	6.75
Spillage (ml)	0.01

Dimensions	IMPERIAL
Port (A)	3/8"
Overall length M+F (in)	F+D-0,63
Length (in)	2,55
Max. diameter (in)	1,26
Weight (lb)	0,61

Caps

Item code	Product name
815100002	PLASTIC CAP F FF38 RED
815200002	PLASTIC FLIP CAP F FF38 RED
816005004	ALUMINUM CAP F FF38 NATURAL
815101002	PLASTIC CAP F FF38 YELLOW**
815102002	PLASTIC CAP F FF38 BLUE**
815103002	PLASTIC CAP F FF38 BLACK**
815104002	PLASTIC CAP F FF38 GREEN**
815107002	PLASTIC CAP F FF38 ORANGE**
815110002	PLASTIC CAP F FF38 MAGENTA**
815201002	PLASTIC FLIP CAP F FF38 YELLOW**
815202002	PLASTIC FLIP CAP F FF38 BLUE**
815203002	PLASTIC FLIP CAP F FF38 BLACK**
815204002	PLASTIC FLIP CAP F FF38 GREEN**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service