

F AX9N 1/2 BSP*

Codice articolo: 808500006 / Female / *Prodotto disponibile su richiesta



Body size 3/8"	Valving style Flat face
Interchange ISO 16028	Sealing Nitrile NBR
Connection system Push	Disconnection system Pull back the sleeve
Material Stainless steel	Locking mechanism Locking ball + Safety lock
Disconnectable under pressure No	Thread FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	Temperature -20 / +100 °C; -4 / +212 °F
Applications Oil & Gas, Industry, Cooling, Chemical & Food industry	

Performance	METRIC	Dimensions	METRIC
ISO DN (mm)	10	Port (A)	1/2"
Flow (l/min)	Da 20 a 50	Overall length M+F (mm)	103 125,7
Max. Flow suggested (l/min)	46	Max. diameter (mm)	32
Max. Operating pressure - coupled (Mpa)	35	Weight (kg)	0,33
Operating pressure - uncoupled (mpa)	35		
Connect force (N)	200		
Disconnect force (N)	45		
Spillage (ml)	0.01		

Related products

Item code	Type	Product name
808500007	Maschio	M AX9N 1/2 BSP

Caps

Item code	Product name
815100002	PLASTIC CAP F FF38 RED
815200002	PLASTIC FLIP CAP F FF38 RED
816005004	ALUMINUM CAP F FF38 NATURAL
815103002	PLASTIC CAP F FF38 BLACK **
815102002	PLASTIC CAP F FF38 BLUE **
815104002	PLASTIC CAP F FF38 GREEN **
815110002	PLASTIC CAP F FF38 MAGENTA **
815107002	PLASTIC CAP F FF38 ORANGE **
815101002	PLASTIC CAP F FF38 YELLOW **
815203002	PLASTIC FLIP CAP F FF38 BLACK **
815202002	PLASTIC FLIP CAP F FF38 BLUE **
815204002	PLASTIC FLIP CAP F FF38 GREEN **
815201002	PLASTIC FLIP CAP F FF38 YELLOW **

**Product available upon request