F AX13N 1/2 BSP

Codice articolo: **808500008** / **Female**

Valving style Flat face	**Body size** 1/2"
Sealing Nitrile NBR	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -20 / +100 °C; -4 / +212 °F
Applications Medical Devices, Semiconductors, Leather, Food & Beverage, Defence, Laser, Electric Vehicles, Digital Transmitters, Injection Moulding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas	

Performance	METRIC
ISO DN (mm)	12.5
Max. Flow suggested (l/min)	90
Max. Operating pressure - coupled (MPa)	33
Operating pressure - uncoupled (MPa)	33
Connect force (N)	165
Disconnect force (N)	58
Spillage (ml)	0.02

Dimensions	METRIC
Port (A)	1/2"
Overall length M+F (mm)	137,1
Length (mm)	76,9
Max. diameter (mm)	38
Weight (kg)	0,48

Related products

Item code	Type	Product name
808500009	Maschio	M AX13N 1/2 BSP

Caps

Item code	Product name
815100004	PLASTIC CAP F FF12 RED
815200004	PLASTIC FLIP CAP F FF12 RED
816005006	ALUMINUM CAP F FF12 NATURAL
815101004	PLASTIC CAP F FF12 YELLOW*
815102004	PLASTIC CAP F FF12 BLUE*
815103004	PLASTIC CAP F FF12 BLACK*
815104004	PLASTIC CAP F FF12 GREEN*
815105004	PLASTIC CAP F FF12 WHITE*
815201004	PLASTIC FLIP CAP F FF12 YELLOW*
815202004	PLASTIC FLIP CAP F FF12 BLUE*
815203004	PLASTIC FLIP CAP F FF12 BLACK*
815204004	PLASTIC FLIP CAP F FF12 GREEN*
815207004	PLASTIC FLIP CAP F FF12 ORANGE*
815208004	PLASTIC FLIP CAP F FF12 BROWN*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service