

M AX9N S16*

Codice articolo: 808509005 / Male / *Prodotto disponibile su richiesta



Body size 3/8"	Valving style Flat face
Interchange ISO 16028	Sealing Nitrile NBR
Connection system Push	Disconnection system Pull back the sleeve
Material Stainless steel	Locking mechanism Locking ball + Safety lock
Disconnectable under pressure No	Thread MALE THREAD METRIC S - 24° CONE (ISO 8434-1 & DIN 2353)
Connectable under residual pressure No	Temperature -20 / +100 °C; -4 / +212 °F
Applications Oil & Gas, Industry, Cooling, Chemical & Food industry	

Performance	METRIC	Dimensions	METRIC
ISO DN (mm)	10	Port (A)	M24X1.5
Flow (l/min)	Da 20 a 50	Overall length M+F (mm)	132,5
Max. Flow suggested (l/min)	46	Length (mm)	72,4
Max. Operating pressure - coupled (Mpa)	35	Max. diameter (mm)	29
Operating pressure - uncoupled (mpa)	35	Weight (kg)	0,17
Connect force (N)	200		
Disconnect force (N)	45		
Spillage (ml)	0.01		

Related products

Item code	Type	Product name
808509004	Femmina	F AX9N S16

Spare kits

Item code	Product name
815700337	SPARE KIT OR NBR+BK M FF 38

Caps

Item code	Product name
815100025	PLASTIC CAP M FF38 RED
816005005	ALUMINUM CAP M FF38 NATURAL
815103025	PLASTIC CAP M FF38 BLACK **
815102025	PLASTIC CAP M FF38 BLUE **
815104025	PLASTIC CAP M FF38 GREEN **
815110027	PLASTIC CAP M FF38 MAGENTA BIG RING **
815107027	PLASTIC CAP M FF38 ORANGE BIG RING **
815105025	PLASTIC CAP M FF38 WHITE **
815101025	PLASTIC CAP M FF38 YELLOW **

**Product available upon request